



SAFETY DATA SHEET

Issuing Date: 03-05-2015

Revision Date: 02-02-2016

Version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code(s): 24316100-M
Product Name DME - Mold Cleaner Aerosol

Recommended use Metal Protection
Uses advised against Any other purpose.

Manufacturer, Importer, Supplier

Houghton International Inc.
Madison & Van Buren Aves.
Valley Forge, PA 19482
Telephone: 610-666-4000 FAX: 610-666-1376
Website: www.houghtonintl.com
Customer Service: 888-459-9844

DME
29111 STEPHENSON HWY
MADISON HEIGHTS, MI 48071
800-626-6653 (U.S.), 800-387-6600 (Canada)
or 248-398-6000 (worldwide)

Emergency telephone number

3E Company 1-866-519-4752 (USA, Canada, Mexico)
Company Access Code: 333938

SECTION 2: Hazards identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 3
Gas Under Pressure	Compressed Gas

GHS Label elements, including precautionary statements

Signal Word

DANGER

Hazard Statements

May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways Flammable Aerosol
Contains gas under pressure; may explode if heated



Precautionary Statements

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Ground/Bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Wear protective gloves/protective clothing/eye protection/face protection
 Do not spray on an open flame or ignition source
 Pressurized container: Do not pierce or burn, even after use
 Keep cool

Precautionary Statements - Response**Skin**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

Prolonged skin contact may defat the skin and produce dermatitis.

SECTION 3: Composition/information on ingredients

This product is a mixture. Health hazard information is based on its ingredients.

Chemical Name	CAS-No	Weight %
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	-	25% - 60%
Distillates (petroleum), hydrotreated light	64742-47-8	25% - 60%
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	2.5% - 10%
Carbon Dioxide	124-38-9	2% - 10%
Paraffin waxes (petroleum), hydrotreated	64742-51-4	1% - 2.5%
2-Methylpentane-2,4-diol	107-41-5	1% - 2.5%
Calcium bis(dinonylnaphthalenesulphonate)	57855-77-3	1% - 2.5%
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	1% - 2.5%

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. See Section 15 for additional information on base oils.

SECTION 4: First aid measures

4.1. Description of first-aid measures**General advice**

Immediate medical attention is required. Do not get in eyes, on skin, or on clothing. Do not breathe dust, fume, gas, mist, vapors, or spray.

Inhalation	Move to fresh air. Potential for aspiration if swallowed. Get medical attention immediately if symptoms occur.
Skin contact	Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.
Ingestion	Do not induce vomiting without medical advice. Clean mouth with water and afterwards drink plenty of water. Aspiration hazard if swallowed - can enter lungs and cause damage. If symptoms persist, call a physician.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

Main Symptoms May be fatal if swallowed and enters airways

4.3. Indication of immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

SECTION 5: Fire Fighting Measures

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment: Use CO₂, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard

In the event of fire and/or explosion do not breathe fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Flammable. Risk of ignition. Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Decomposition Products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect against bursting containers

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Keep people away from and upwind of spill/leak.

Advice for non-emergency Eliminate all ignition sources if safe to do so. Evacuate personnel to safe areas.

Personnel

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills. After cleaning, flush away traces with water.

6.4. Reference to other sections

See Section 8/12/13 for additional information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Remove all sources of ignition. Keep away from open flames, hot surfaces and sources of ignition. Unplug tools, appliances and motors before spraying. Do not allow can to touch any source of electricity. Do not puncture, crush or incinerate containers, even when empty.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Do not store above 120 °F or in direct sunlight. Keep out of the reach of children.

Recommended Shelf Life

No information available.

Incompatible Materials

Strong oxidizing agents, Strong acids, Strong bases

7.3. Specific end uses

Specific use(s) Metal Protection

SECTION 8: Exposure controls/personal protection

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	AIHA WEEL
Highly refined, low viscosity base oil (Viscosity <7 cSt@40°C) -	5 mg/m ³ as mist	5 mg/m ³ as mist		
Highly refined base oil (Viscosity >20.5 cSt @40°C) -	5 mg/m ³ as mist	5 mg/m ³ as mist		
Paraffin waxes (petroleum), hydrotreated 64742-51-4	5 mg/m ³ as mist	5 mg/m ³ as mist		
2-Methylpentane-2,4-diol 107-41-5	Ceiling: 25 ppm	(vacated) Ceiling: 25 ppm (vacated) Ceiling: 125 mg/m ³	Ceiling: 25 ppm Ceiling: 125 mg/m ³	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt@40°C) -	5 mg/m ³ as mist	5 mg/m ³ as mist		
Carbon Dioxide 124-38-9	5,000 ppm	5,000 ppm		

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Hydrocarbon solvent vapor mixtures which do not have substance specific occupational exposure limits may be evaluated by the Reciprocal Calculation Procedure (RCP) which assigns a recommended occupational exposure limit based on the mass composition and hydrocarbon group guidance values (GGVs). Applicable recommended occupational exposure limits are shown in the table below.

Chemical Name	RCP OEL	Manufacturer
Distillates (petroleum), hydrotreated middle 64742-46-7	RCP: TWA 1200 mg/m ³ 143ppm	
Distillates (petroleum), hydrotreated light 64742-47-8	RCP: TWA 1200 mg/m ³ 182ppm	
Naphtha (petroleum), hydrotreated heavy 64742-48-9	RCP: TWA 1000 mg/m ³	
C12-C14 isoalkanes 68551-19-9	RCP: TWA 1200 mg/m ³	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 600 mg/m ³	
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0.03% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 150ppm TWA: 1200 mg/m ³	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOT AVAILABLE	TWA: 171 ppm TWA: 1200 mg/m ³	
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 165 ppm TWA: 1200 mg/m ³	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP: TWA 1200 mg/m ³ 182ppm	
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	
Carbon Dioxide 124-38-9	TWA 5000 ppm STEL: 30,000 ppm 15-min	

Exposure controls**Engineering Measures**

Showers.
Eyewash stations.
Ventilation systems.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Safety glasses with side-shields. Avoid spraying in your face.

Skin and body protection

Wear protective gloves/clothing.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state @20°C Liquid
Odor Perfumes
Appearance Clear, Dark
Odor Threshold Not Applicable

Property	Values	Note
pH	No information available	
Melting Point/Freezing Point	No information available	
Boiling point/Boiling range	< 93 °C / < 199 °F	
Flash point	41 °C / 106 °F	PMCC
Evaporation rate	No information available	
Flammability (solid, gas)	Flammable Aerosol	
Flammability Limits in Air		
Upper flammability limit	0.06%	
Lower flammability limit	8%	
Vapor pressure	838 psig @ 21.1 °C / 70 °F	
Vapor density	Grater than 1	air = 1
Relative density	0.83	
Solubility(ies)	Insoluble in water	
Partition coefficient: n-octanol/water	Not Applicable	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Viscosity, kinematic	< 5 cSt @ 40 °C	
Explosive properties	Contents under pressure	
Oxidizing Properties	Not Applicable	

9.2. Other information

Property	Values	Note
Viscosity, kinematic (100°C)	No information available	
Pour point	No information available	
VOC Content	722 g/L	ASTM E 1868-10

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal use conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity, Keep away from open flames, hot surfaces and sources of ignition, do not puncture or incinerate containers

10.5. Incompatible Materials

Strong oxidizing agents, Strong acids, Strong bases

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

Information on likely routes of exposure

Product Information	May be harmful if swallowed and enters airways
Inhalation	Risk of serious damage to the lungs (by aspiration).
Eye contact	May be irritating to eyes. May cause redness and tearing.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Ingestion	Risk of product entering the lungs on vomiting after ingestion.

Component Information

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined, low viscosity base oil (Viscosity <7 cSt@40°C) -	>2000 mg/kg	>2000 mg/kg	
Distillates (petroleum), hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Highly refined base oil (Viscosity >20.5 cSt @40°C) -	>2000 mg/kg	>2000 mg/kg	
Paraffin waxes (petroleum), hydrotreated 64742-51-4	10000 mg/kg (Rat)	> 3600 mg/kg (Rabbit)	
2-Methylpentane-2,4-diol 107-41-5	3692 mg/kg (Rat)	= 8560 µL/kg (Rabbit)	> 310 mg/m ³ (Rat) 1 h
Calcium bis(dinonylnaphthalenesulphonate) 57855-77-3	>4000 mg/kg (Rat)		
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt@40°C) -	>2000 mg/kg	>2000 mg/kg	
Carbon Dioxide 124-38-9			100,000 ppm/min

Information on toxicological effects

Symptoms Prolonged skin contact may defat the skin and produce dermatitis.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	None known.
Germ Cell Mutagenicity	None known.
Carcinogenicity	None known.
Reproductive toxicity	None known.
Specific target organ systemic toxicity (single exposure)	May cause disorder and damage to the. Central nervous system (CNS). May cause drowsiness or dizziness.
Specific target organ systemic toxicity (repeated exposure)	None known.
Aspiration hazard	Risk of serious damage to the lungs (by aspiration).

SECTION 12: Ecological information

Ecotoxicity

No special environmental measures are necessary.

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
Distillates (petroleum), hydrotreated light	1000: 72 h Pseudokirchneriella subcapitata mg/L EC50	1000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
2-Methylpentane-2,4-diol	>420: 72 h Selenastrum capricornutum mg/l EC50	10500-11000: 96 h Pimephales promelas mg/L LC50 flow-through 10000: 96 h Lepomis macrochirus mg/L LC50 static 8690: 96 h Pimephales promelas mg/L LC50 flow-through 10700: 96 h Pimephales promelas mg/L LC50 static		2700 - 3700: 48 h Daphnia magna mg/L EC50

Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

Bioaccumulation

Chemical Name	log Pow
2-Methylpentane-2,4-diol 107-41-5	0.14

Other adverse effects

No information available.

SECTION 13: Disposal considerations

Waste treatment**Waste Disposal Methods**

Do not puncture or incinerate containers, even empty. Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging

Observe all label precautions until container is cleaned, reconditioned or destroyed.

SECTION 14: Transport information

DOT

UN/ID	UN1950
Proper shipping name	Aerosols, 2.1, LTD QTY
Hazard class	2.1
Packing group	N/A
Special Provisions	N82
Exceptions	306
Description	UN1950, Aerosols, 2.1, LTD QTY
Emergency Response Guide Number	126
Notes	<p>Ground Shipment: Shipping Description: "Consumer Commodity" ORM-D (This shipping description is only good until December 31, 2020. Shipping Papers are not required for Consumer Commodities.)</p> <p>Air shipments: This product is not recommended for air shipments.</p>

ICAO/IATA

UN No.	UN1950
Proper shipping name	Aerosols, 2.1, LTD QTY
Hazard class	2.1
Packing group	N/A
Description	UN1950 Aerosols, 2.1, LTD QTY

IMDG/IMO

UN No.	UN1950
Proper shipping name	Aerosols, 2, LTD QTY
Hazard class	2
Packing Group	N/A
Description	UN1950 Aerosols, 2, LTD QTY

SECTION 15: Regulatory information**International Inventories**

TSCA	Complies
DSL	Complies
AICS	Complies
PICCS	Complies
KECL	Complies
IECSC	Complies
ENCS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

ENCS - Japan Existing and New Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	no
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**SCAQMD Rule 1144**

This product exceeds VOC concentrations set by SCAQMD as determined by test method ASTM E1868-10 and cannot be used as a metal working fluid or as a direct contact lubricant in California's SCAQMD region as per rule 1144.

California Proposition 65

This product does not contain any Proposition 65 chemicals.

International Regulations

Mexico - Grade Moderate risk, Grade 2

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard ClassD2B Toxic materials
B3 Combustible liquidClass A (Compressed gas)
Class B-5 (Flammable Aerosol)**Other information**

Not applicable

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated	101316-72-7
Lubricating oils (petroleum), used, noncatalytically refined	101316-73-8
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4
Residual oils (petroleum), solvent-refined	64742-01-4
Extracts (petroleum), residual oil solvent	64742-10-5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Residual oils (petroleum), hydrotreated	64742-57-0
Lubricating oils (petroleum), hydrotreated spent	64742-58-1
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
Lubricating oils	74869-22-0
Paraffin oils	8012-95-1
White mineral oil (petroleum)	8042-47-5

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No
Distillates (petroleum), straight-run middle	64741-44-2
Distillates (petroleum), heavy hydrocracked	64741-76-0
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5
Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
White mineral oil (petroleum)	8042-47-5
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE

The highly refined, low viscosity base oil (Viscosity <7 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No
Distillates (petroleum), hydrotreated middle	64742-46-7
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Naphtha (petroleum), hydrotreated heavy	64742-48-9
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9
C12-C14 isoalkanes	68551-19-9
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9
Alkanes, C14-16	90622-46-1
Alkanes, C12-26-branched and linear	90622-53-0
Alkanes, C11-15-iso-	90622-58-5
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	NOT AVAILABLE
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C11-C14, n-alkanes, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C14-C18, n-alkanes, cyclics, aromatics (2-30%)	NOT AVAILABLE
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C13-C16, isoalkanes, cyclics, < 2% aromatics	NOT AVAILABLE
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	NOT AVAILABLE
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE

SECTION 16: Other information

NFPA	Health Hazard 3	Flammability 2	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 3	Flammability 2	Physical Hazard 0	Personal protection X

Key or legend to abbreviations and acronyms used in the safety data sheet

STOT SE - Specific target organ systemic toxicity (Single exposure)
 STOT RE - Specific target organ systemic toxicity (repeated exposure)
 TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 VOC - Volatile organic compounds
 NIOSH IDLH: Immediately Dangerous to Life or Health

Issuing Date: 03-05-2015
 Revision Date: 03-05-2015
 Revision Note

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End