

DME Standard DME Single Zone Timer NEW PRODUCT BULLETIN

Versatile for virtually any type of operation that requires a timer, including single-zone valve gate systems, core pulls, and air sweeps.

Benefits:

- Unit plugs directly into DME Smart Series Mainframes
- Test button (green light indicates power out)
- Yellow light indicates trigger signal being applied or timer in operation
- Trigger signal has two available sources – dry set of contacts or 24 VDC input
- Trigger input signal can be ganged to operate more than one timer when multiple units are used (24 VDC input only)
- Input signal and output power can be used from timer front panel connectors or DME mainframe cables
- Thermocouple cable serves as trigger signal; power cable serves as 24 VDC power supply to any 24 VDC solenoid valve

DME Single Zone Timers (TCM-03-024D) are highly accurate, solid state timers that feature resolution to 1/100 of second, far exceeding the industry standard of 1/10 of a second.



DME Single Zone Timer: TCM-03-024D

Shown Next to a SSM-15-12 Temperature Controller
in a Standard 2 Zone Smart Series Mainframe.

DME
Every step of the way

World Headquarters

DME Company

29111 Stephenson Highway
Madison Heights, MI 48071
800-626-6653 toll-free tel
248-398-6000 V
888-808-4363 toll-free fax
www.dme.net web
info@dme.net e-mail

DME of Canada, Ltd.

6210 Northwest Drive
Mississauga, Ontario
Canada L4V 1J6
800-387-6600 toll-free tel
905-677-6370 tel
800-461-9965 toll-free fax
dme_canada@dme.net e-mail

DME Europe

D-M-E Belgium C.V.B.A.
Industriepark Noord
B-2800 Mechelen
Belgium
32-15-215011 tel
32-15-218235 fax
sales@dmeeu.com e-mail