

RT-Series Collapsible Cores

Standard and Mini Collapsible Cores



Standard - Economically produce complex plastic parts

The Collapsible Core is a major breakthrough for molding plastic parts requiring internal threads, undercuts, protrusions or cut-outs. The patented design incorporates only three moving parts, which utilize conventional mold movements.

The Collapsible Core's automatic operation makes it possible for you to produce parts that, previously, had been considered impossible to mold. Parts with internal protrusions, dimples, interrupted threads and cut-outs can now be economically produced on a high- or low-volume basis.

ITEM NUMBER	A MAX O.D. OF THREAD OR CONFIG		B MIN I.D. OF THREAD OR CONFIG		H CENTER PIN DIAMETER (AT TOP OF CORE)		L MAX WORKING LENGTH (INCL MOLD SHUT-OFF)		C COLLAPSE PER SIDE AT TOP OF CORE**				O.A.L. OVERALL LENGTH OF COLLAPSIBLE CORE (ONLY)	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	*inch	*mm	inch	mm
CC125PC	.720	18.29	.620	15.75	.490	12.45	.800	20.32	.027	.69	.032	.81	5.605	142.37
CC150PC	.850	21.59	.700	17.78	.580	14.73	1.000	25.40	.037	.94	.042	1.07	6.615	168.02
CC175PC	.970	24.64	.760	19.30	.640	16.26	1.000	25.40	.043	1.09	.048	1.21	6.615	168.02
CC200PC	1.270	32.25	.910	23.11	.785	19.93	1.150	29.21	.043	1.09	.048	1.21	7.315	185.80
†CC250PC	1.270	32.25	.910	23.11	.785	19.93	1.150	29.21	.043	1.09	.048	1.21	5.440	138.17
CC202PC	1.390	35.30	1.010	25.65	.885	22.47	1.150	29.21	.055	1.39	.064	1.62	7.315	185.80
†CC252PC	1.390	35.30	1.010	25.65	.885	22.47	1.150	29.21	.055	1.39	.064	1.62	5.440	138.17
CC302PC	1.740	44.19	1.270	32.25	1.105	28.06	1.400	35.56	.068	1.72	.083	2.10	7.315	185.80
†CC352PC	1.740	44.19	1.270	32.25	1.105	28.06	1.400	35.56	.068	1.72	.083	2.10	6.065	154.05
CC402PC	2.182	55.42	1.593	40.46	1.388	35.25	1.700	43.18	.090	2.28	.103	2.61	7.815	198.50
CC502PC	2.800	71.12	2.060	52.32	1.750	44.45	1.900	48.26	.115	2.92	.125	3.17	9.625	244.47
CC602PC	3.535	89.78	2.610	66.29	2.175	55.24	2.400	60.96	.140	3.55	.148	3.75	11.250	285.75
CC652PC	3.800	96.52	2.890	73.41	2.450	62.23	2.400	60.96	.150	3.81	.160	4.06	11.250	285.75
CC702PC	4.225	107.31	3.350	85.09	2.875	73.02	2.400	60.96	.165	4.19	.170	4.32	11.250	285.75

Mini - Easily mold parts with closures as small as 13mm

The Collapsible Mini-Core broadens the applications of collapsible core molds for closures as small as 13mm. Due to the smaller diameters involved, these Mini-Cores employ three larger collapsing segments combined with three narrow, non-collapsing blades, which are an integral part of the center pin.

As a result, up to 80% full threads or undercuts can be molded. The function of the collapsing core also permits threads to stop at any point along the molded length – threads need not run out to the top of the core as with unscrewing molds. If a seal is required in the top of the closure, an undercut can be molded into the part to hold such a seal in place.

Three standard sizes of Collapsible Mini-Cores are available, for 13-16, 17-20 and 21-24mm closures.

ITEM NUMBER	FOR CLOSURE DIAMETER RANGE	A MAX O.D. OF THREAD OR CONFIG		B MIN I.D. OF THREAD OR CONFIG		H CENTER PIN DIAMETER (AT TOP OF CORE)		WIDTH OF (3) NON-COLLAPSING CENTER OF PIN BLADES (AT TOP OF CORE)		L MAX WORKING LENGTH (INCL MOLD SHUT-OFF)		C COLLAPSE PER SIDE AT TOP OF CORE*	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
CCM0001	13-16	.645	16.38	.425	10.80	.300	7.62	.170	4.32	.850	21.59	.052	1.32
CCM0002	17-20	.805	20.45	.560	14.22	.420	10.67	.190	4.83	.850	21.59	.057	1.45
CCM0003	21-24	.965	24.51	.710	18.03	.560	14.22	.200	5.08	1.000	25.40	.059	1.50