SDS Revision Date: 07/25/2017

1. Identification

1.1. Product identifier

Product Identity DME - Mold Cleaner Aerosol
Alternate Names DME - Mold Cleaner Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Metal Protection.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name DME Co

29111 STEPHENSON HWY MADISON HEIGHTS, MI 48071

Emergency

24 hour Emergency Telephone No. US CHEMTREC number 1-800-424-9300

Outside the US (Canada) number 1-703-527-

3887

Mexico 1-800-681-9531 (CHEMTREC)

Customer Service: DME Co 800-626-6653 (U.S.), 800-387-6600 (Canada)

or 248-398-6000 (worldwide)

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222 Extremely flammable aerosol.

Press. Gas;H280 Contains gas under pressure; may explode if heated.

Skin Irrit. 3;H316 Causes mild skin irritation. (Not adopted by US OSHA)

Skin Sens. 1;H317 May cause an allergic skin reaction.

Asp. Tox. 1;H304 May be fatal if swallowed and enters airways.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.

2.2. Label elements



Danger

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

07/25/2017 **SDS Revision Date:**

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

May displace oxygen and cause rapid suffocation.

Pressurized container: May burst if heated.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (see information on this label).

P331 Do NOT induce vomiting.

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P363 Wash contaminated clothing before reuse.

[Storage]:

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|--|----------|--|--------|
| Distillates (petroleum), hydrotreated light CAS Number: 0064742-47-8 | 75 - 100 | Asp. Tox. 1;H304 | [1] |
| Carbon dioxide CAS Number: 0000124-38-9 | 5 - 10 | Press. Gas;H280 Simple Asphyxiant | [1][2] |
| 2-methylpentane-2,4-diol CAS Number: 0000107-41-5 | 1 - 5 | Eye Irrit. 2;H319 Skin Irrit. 2;H315 | [1][2] |
| Naphthalenesulfonic acid, dinonyl-, calcium salt CAS Number: 0057855-77-3 | 1 - 5 | Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens. 1;H317 | [1] |
| Paraffin waxes (petroleum), hydrotreated CAS Number: 0064742-51-4 | 1 - 5 | Not Classified | [1] |

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

^[1] Substance classified with a health or environmental hazard.

^[2] Substance with a workplace exposure limit.

^[3] PBT-substance or vPvB-substance.
*The full texts of the phrases are shown in Section 16.

SDS Revision Date: 07/25/2017

Section 4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or

stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids

apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water

or use a recognized skin cleanser.

Ingestion If accidentally swallowed obtain immediate medical attention. Keep at rest.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview Exposure to solvent vapor concentrations from the component solvents in

excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible

reversible damage. See section 2 for further details.

Inhalation May be fatal if swallowed and enters airways.

Skin May cause an allergic skin reaction. Causes mild skin irritation

Section 5. Fire-fighting measures

5.1. Extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment: Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray. Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust / fume / gas / mist / vapors / spray.

SDS Revision Date: 07/25/2017

5.3. Advice for fire-fighters

In the event of fire and/or explosion do not breathe fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Flammable. Risk of ignition. Thermal decomposition can lead to release of irritating gases and vapors.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect against bursting containers

ERG Guide No. 126

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills. After cleaning, flush away traces with water.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Remove all sources of ignition. Keep away from open flames, hot surfaces and sources of ignition. Unplug tools, appliances and motors before spraying. Do not allow can to touch any source of electricity. Do not puncture, crush or incinerate containers, even when empty.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Do not store above 120 °F or in direct sunlight. Keep out of the reach of children.

Incompatible materials: Strong oxidizing agents, Strong acids, Strong bases.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

SDS Revision Date: 07/25/2017

Section 8. Exposure controls and personal protection

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|--|----------|--|
| 0000107-41-5 | 2-methylpentane-2,4-diol | OSHA | No Established Limit |
| | | ACGIH | Ceiling: 25 ppm |
| | | NIOSH | C 25 ppm (125 mg/m3) |
| | | Supplier | No Established Limit |
| 0000124-38-9 | Carbon dioxide | OSHA | TWA 5000 ppm (9000 mg/m3) |
| | | ACGIH | TWA: 5000 ppm Ceiling: 15000 ppm |
| | | NIOSH | TWA 5000 ppm (9000 mg/m3) ST 30,000 ppm (54,000 mg/m3) |
| | | Supplier | No Established Limit |
| 0057855-77-3 | Naphthalenesulfonic acid, dinonyl-, calcium salt | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0064742-47-8 | Distillates (petroleum), hydrotreated light | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | Recommended 300 ppm PEL |
| 0064742-51-4 | Paraffin waxes (petroleum), hydrotreated | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

8.2. Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must

use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Protective gloves recommended.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must

be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking,

smoking or using toilet. Promptly remove soiled clothing and wash

thoroughly before reuse.

SDS Revision Date: 07/25/2017

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance Clear, Dark Pressurized aerosol dispensed as a

mist.

Odor Perfumed

Odor threshold

PH

Not Measured

1014 1 °C / 106 °F

Not Measured

Not Measured

Not Measured

Not Measured

Not Measured

Not Measured

Not Applicable

Upper/lower flammability or explosive limits

Lower Explosive Limit: No information

available

Upper Explosive Limit: No information

available

Vapor pressure (Pa)No information availableVapor DensityNo information available

Specific Gravity 0.83

Solubility in Water Not Measured

Partition coefficient n-octanol/water (Log

Kow)

Not Measured

Auto-ignition temperatureNot MeasuredDecomposition temperatureNot MeasuredViscosity (cSt)< 5 cSt @ 40 °C</th>

VOC Content 722 g/L ASTM E 1868-10

9.2. Other information

No other relevant information.

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

SDS Revision Date: 07/25/2017

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity, Keep away from open flames, hot surfaces and sources of ignition, do not puncture or incinerate containers.

10.5. Incompatible materials

Strong oxidizing agents, Strong acids, Strong bases.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LC50, mg/L/4hr | Inhalation Dust/Mist LC50, mg/L/4hr | Inhalation Gas LC50, ppm |
|---|---|--|---------------------------------------|---|--------------------------------|
| Distillates (petroleum), hydrotreated light - (64742-47-8) | > 5,000.00, Rat - Category: NA | >2,000.00, Rabbit - Category: 5 | No data available | No data available | No data available |
| Carbon dioxide - (124-38-9) | No data available | No data available | No data available | No data available | No data available |
| 2-methylpentane-2,4-diol - (107-41-5) | 3,700.00, Rat - Category: 5 | 7,892.00, Rabbit - Category: NA | No data available | No data available | No data available |
| Naphthalenesulfonic acid, dinonyl-, calcium salt - (57855-77-3) | No data available | No data available | No data available | No data available | No data available |
| Paraffin waxes (petroleum), hydrotreated - (64742-51-4) | No data available | No data available | No data available | No data available | No data available |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|--------------------------|--------|--|
| 0000107-41-5 | 2-methylpentane-2,4-diol | OSHA | Regulated Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

SDS Revision Date:

07/25/2017

| 0000124-38-9 | Carbon dioxide | OSHA | Regulated Carcinogen: No | |
|--|---------------------------|------|--|--|
| | | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | |
| 0057855-77-3 | Naphthalenesulfonic acid, | OSHA | Regulated Carcinogen: No | |
| dinonyl-, calcium salt | | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | |
| 0064742-47-8 Distillates (petroleum), hydrotreated light | | OSHA | Regulated Carcinogen: No | |
| | | NTP | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | |
| 0064742-51-4 | Paraffin waxes | OSHA | Regulated Carcinogen: No | |
| | (petroleum), hydrotreated | | Known: No; Suspected: No | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | |

| Classification | Category | Hazard Description |
|-------------------------------|----------|---|
| Acute toxicity (oral) | | Not Applicable |
| Acute toxicity (dermal) | | Not Applicable |
| Acute toxicity (inhalation) | | Not Applicable |
| Skin corrosion/irritation | 3 | Causes mild skin irritation. (Not adopted by US OSHA) |
| Serious eye damage/irritation | | Not Applicable |
| Respiratory sensitization | | Not Applicable |
| Skin sensitization | 1 | May cause an allergic skin reaction. |
| Germ cell mutagenicity | | Not Applicable |
| Carcinogenicity | | Not Applicable |
| Reproductive toxicity | | Not Applicable |
| STOT-single exposure | | Not Applicable |
| STOT-repeated exposure | | Not Applicable |
| Aspiration hazard | 1 | May be fatal if swallowed and enters airways. |

Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, | 48 hr EC50 crustacea, | ErC50 algae, |
|------------|------------------|-----------------------|--------------|
| | mg/l | mg/l | mg/l |
| | 9/ | | |

SDS Revision Date:

07/25/2017

| Distillates (petroleum), hydrotreated light - (64742-47-8) | 45.00, Pimephales promelas | 4,720.00, Dendronereides heteropoda | Not Available |
|---|-----------------------------------|-------------------------------------|---------------|
| Carbon dioxide - (124-38-9) | Not Available | Not Available | Not Available |
| 2-methylpentane-2,4-diol - (107-41-5) | 10,000.00, Lepomis macrochirus | 2,800.00, Cerodaphnia reticulata | Not Available |
| Naphthalenesulfonic acid, dinonyl-, calcium salt - (57855-77-3) | Not Available | Not Available | Not Available |
| Paraffin waxes (petroleum), hydrotreated - (64742-51-4) | Not Available | Not Available | Not Available |

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

| | DOT (Domestic Surface Transportation) | IMO / IMDG (Ocean Transportation) | ICAO/IATA | | |
|------------------------------------|---|---|-------------------------------|--|--|
| 14.1. UN number | UN1950 | UN1950 | UN1950 | | |
| 14.2. UN proper shipping name | UN1950, Aerosols, Limited Quantity, 2.1, NA | Aerosols, Limited Quantity | Aerosols, Limited Quantity | | |
| 14.3. Transport hazard class(es) | DOT Hazard Class: 2.1 | IMDG: 2.1 Sub Class: Not Applicable | Air Class: 2.1 | | |
| 14.4. Packing group | Not Applicable | Not Applicable | Not Applicable | | |
| 14.5. Environmental hazards | | | | | |
| IMDG Marine Pollutant: No; | | | | | |
| 14.6. Special precautions for user | | | | | |
| No | further information | | | | |

SDS Revision Date: 07/25/2017

Section 15. Regulatory information

Regulatory The regulatory data in Section 15 is not intended to be all-inclusive, only

Overview selected regulations are represented.

Toxic Substance All components of this material are either listed or exempt from listing on the

Control Act (TSCA) TSCA Inventory.

WHMIS 1988 A B5 D2B

Classification

US EPA Tier II Fire: No

Hazards

Sudden Release of Pressure: Yes

Reactive: No Immediate (Acute): Yes Delayed (Chronic): No

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

SDS Revision Date: 07/25/2017

Section 16. Other information

SDS Revision Date 07/25/2017

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

The information contained herein is furnished without warranty of any kind. The above information is believed to be correct but does not purport to be all inclusive and should be used only as a guide. Users should make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.

End of Document