

# DYNA-PURGE E2 Safety Data Sheet

Revision Date: 7 Aug 2016 Version: 3.0

#### Section 1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product Identifier: Product Name: Product Form:	Dyna-Purge E2 Mixture of pellets	
1.2 Product Use:	Thermoplastic Purging Compound	
1.3 Manufacturer: Address: Phone / Fax:	Shuman Plastics 35 Neoga Street Depew, NY 14043 (716) 685-2121 / (716) 685-3236	
1.4 Emergency Phone:	(716) 685-2121	
1.5 Transportation Emergency Phone:	Chemtrec Emergency Number (800)424-9300 (US); (703)527-3887 (outside US)	
Section 2. HAZARDS IDENTIFICATION		
Section 2. HAZARDS IDENT	IFICATION	
2.1 Classification:	Not classified as hazardous under established regulatory criteria OSHA Standard 29CFR- 1910.1200 and CLP-Regulation (EC) No 1272/2008. Not classified as dangerous under EU Directive 67/548/EEC. Not assessed as PBT or vPvB substances according to Regulation (EC) No 1907/2006, Annex XIII.	
	Not classified as hazardous under established regulatory criteria OSHA Standard 29CFR- 1910.1200 and CLP-Regulation (EC) No 1272/2008. Not classified as dangerous under EU Directive 67/548/EEC. Not assessed as PBT or vPvB substances according to	
2.1 Classification:	Not classified as hazardous under established regulatory criteria OSHA Standard 29CFR- 1910.1200 and CLP-Regulation (EC) No 1272/2008. Not classified as dangerous under EU Directive 67/548/EEC. Not assessed as PBT or vPvB substances according to Regulation (EC) No 1907/2006, Annex XIII. In accordance with OSHA and CLP regulations, no labeling, including signal word, hazard	
<ul><li>2.1 Classification:</li><li>2.2 Label Elements:</li></ul>	Not classified as hazardous under established regulatory criteria OSHA Standard 29CFR- 1910.1200 and CLP-Regulation (EC) No 1272/2008. Not classified as dangerous under EU Directive 67/548/EEC. Not assessed as PBT or vPvB substances according to Regulation (EC) No 1907/2006, Annex XIII. In accordance with OSHA and CLP regulations, no labeling, including signal word, hazard	

- Skin: Possible skin irritation. Heated material can cause thermal burns.
- Eyes: Dust may cause irritation. Vapors from heated material may cause irritation. Heated material can cause thermal burns.

#### Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

#### 3.1 Substances: Not applicable

3.2 Mixtures: High molecular weight polymers classified as non-hazardous under OSHA Hazard Communication Standard 29CFR-1910.1200 and CLP-Regulation (EC) No 1272/2008 [CLP].

FDA Compliant ingredients (CFR Title 21, Part 177)

# Section 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

Inhalation:	Remove to fresh air. If breathing difficulty persists, get medical attention.
Eye contact:	Flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation occurs.
Skin contact:	Wash with soap and water. If burned by contact with hot material, flush skin with large amounts of water. Do not attempt to peel hot polymer from skin. Thermal burns require immediate medical attention.
Ingestion:	Wash out mouth with water. Do not induce vomiting unless directed by medical personnel. Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

Inhalation:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Eye contact:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Skin contact:	No known significant effects or critical hazards.
Ingestion:	No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Inhalation:	Adverse symptoms may include respiratory tract irritation and coughing.
Eye contact:	Adverse symptoms may include irritation and redness.
Skin contact:	No specific data.
Ingestion:	No specific data.
4.3 Indication of any immediate	e medical attention and special treatment needed
Notes to physician:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments:	No specific treatment.
Section 5. FIRE FIGHTING MEASURES	

- 5.1 Extinguishing Media: Water spray (fog), foam or dry chemical. Do not use water jet.
- 5.2 Special Exposure Hazards: High dust concentrations have a potential for combustion or explosion. Heated material can form flammable vapors and irritating gases. Hazardous thermal decomposition products may include carbon dioxide, carbon monoxide, methyl methacrylate and low levels of aldehydes, ketones, organic acids or hydrocarbons.

#### 5.3 Special Protective

Equipment for Fire Fighters: Full protective clothing and NIOSH / MHSA approved self-contained breathing apparatus.

# Section 6. ACCIDENTAL RELEASE MEASURES

6.1	Personal Precautions:	May be slippery; use care to avoid falling. Avoid breathing dust and vapor.
6.2	Environmental Precautions:	Avoid dispersal of spilled material and runoff, and contact with soil, waterways, drains and sewers. Avoid creating dusty conditions and prevent wind dispersal.
6.3	Method for Clean Up:	Vacuum or sweep up material and place in a designated labeled waste container. Keep dust to a minimum. Dispose of via a licensed waste disposal contractor.

### Section 7. HANDLING AND STORAGE

7.1	Precautions for safe handling:	When handling hot material, wear heat resistant protective gloves, clothing and face shield that are able to withstand the temperature of the heated product. Do not inhale fumes or vapors from molten product. Avoid creating dust. Use adequate ventilation.
7.2	Conditions for safe storage, including any incompatibilities:	Keep container closed. Store in a cool, well-ventilated area. Keep away from heat and direct sunlight. Incompatible with strong acids and oxidizers.
7.3	Specific end use(s):	Thermoplastic purging compound.

# Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters:	Particulates ACGIH TLV (United States)
	TWA: 10 mg/m <sup>3</sup> 8 hour(s). Form: Inhalable
	TWA: 3 mg/m <sup>3</sup> 8 hour(s). Form: Respirable fraction

Methyl methacrylate (CAS # 80-62-6) ACGIH TLV: 50 ppm, 410 mg/m<sup>3</sup> 8 hours; STEL 100 ppm OSHA: PEL 100 ppm, 410 mg/m<sup>3</sup> 8 hours

8.2 Exposure Controls: Provide local ventilation or other engineering controls to keep airborne contaminants below any recommended or statutory exposure limits. Proper purging and shutdown procedures should be followed to avoid overheating. Keep purge piles small and purge into a vessel of water to solidify used compound and minimize vapors. Use good industrial housekeeping and hygiene practices.

#### Individual protection measures

Respiratory:	Processing may produce dust and/or fumes. To minimize the risk of overexposure, it is recommended that a local exhaust system is placed above the equipment and that the working area is properly ventilated. If ventilation is inadequate, use certified respirator.
Eyes / Face:	If heated, wear safety glasses with side shields or face shield.
Hands / Skin:	Hot Material: Wear heat resistant protective gloves. Cold Material: None required; however, use of protective clothing is good industrial practice.

#### Section 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

Appearance

Physical State:	Solid pellets and granules
Color:	Clear to opaque

Odor: Odor Threshold: pH: Melting/Freezing Point: Boiling Point: Flash Point: Evaporation Rate: Flammability: Vapor Pressure: Vapor Density: Density: Solubility in water: Partition Coefficient, n-octanol/water:	Odorless or mild odor Not available Not available 110°-150°C (230°-300°F) Not available Not available Not available Not available Not available Not available 0.92 – 1.18 Negligible
	No test data available 390°C (734°F) No test data available Not available
9.2 Other Information:	No additional information

# Section 10. STABILITY AND REACTIVITY

10.1 Reactivity	No test data available
10.2 Chemical Stability:	Stable
10.3 Possibility of Hazardous Reactions:	Will not occur under normal conditions of storage and use.
10.4 Conditions to Avoid:	Stable under recommended storage and handling conditions. If heated >300°C, may form vapors or fumes which could cause irritation of the respiratory tract, coughing and shortness of breath. Keep away from open flame.
10.5 Incompatible Materials:	Strong acids and oxidizing agents
10.6 Hazardous Decomposition Products:	Thermal decomposition products are carbon monoxide and/or carbon dioxide and methyl methacrylate. Low levels of aldehydes, ketones, organic acids or hydrocarbons may be formed.

# Section 11. TOXICOLOGICAL INFORMATION

11.1 Acute toxicity	No data available
11.2 Inhalation	No data available
11.3 Dermal	No data available
11.4 Skin corrosion/irritation	No data available
11.5 Eye damage/irritation	No data available
11.6 Respiratory or Skin Sensitivity	No data available
11.7 Carcinogenicity	No component of this product at levels >0.1% is identified as a carcinogen by ACGIH, NTP, OSHA or IARC.
11.8 Reproductive Toxicity	No data available

Section 12. ECOLOGICAL INFORMATION				
12.1 Eco-toxicity	No data available			
12.2 Persistence and Degradability	No data available			
12.3 Bioaccumulative Potential	No data available			
12.4 Mobility in Soil	No data available			
12.5 Results for PBT and vPvB Assessment	This product does not contain substances identified as PBT/vPvB			
12.6 Other Adverse Effects	No specific data available. Do not allow to penetrate soil, waterbodies or drains			
Section 13. DISPOSAL CONSIDERATIONS				
13.1 Waste Disposal:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Dispose of in accordance with all applicable local and national regulations.			
13.2 RCRA Classification:	Not hazardous under RCRA 40 CFR Part 261.			
Section 14. TRANSPORT INFORMATION				

### 14.1 UN number not regulated

14.2 Not regulated for transport (IMO/IMDG, IATA/ICAO, ADR/RID, DOT, TDG, Mexico)

#### Section 15. REGULATORY INFORMATION

15.1 US Federal Regulations:	United States Inventory (TSCA 8b): All components are listed or exempted. SARA Title III 302 extremely hazardous materials: No products were found. SARA Title III 311/312 hazardous materials: No products were found. SARA Title III 313 toxic chemicals: Does not contain any chemical components with known CAS numbers that exceed the threshold (Di Minimus) reporting levels.		
15.2 WHMIS (Canada):	Not controlled under WHMIS.		
15.3 FDA:	FDA compliant ingredients (CFR Title 21, Part 177)		
15.4 REACH:	All components pre-registered, registered, or exempted, according to regulation.		
15.5 REACH SVHCs:	No SVHCs intentionally added.		
15.6 WEEE/RoHS2:	Does not contain any substances classified as hazardous.		
15.7 Global Inventories:	On inventory with: TSCA, IECSC, DSL, ENCS, EINECS, KECI, AICS, PICCS, NZIoC, NECI		

## Section 16. OTHER INFORMATION

16.1 Hazardous Material	Health: 0	Flammability: 1 is responsible for dete	Physical Hazards: 0
Information System:	The customer		ermining the PPE code for this material.
16.2 National Fire Protection System:	Health: 0	Flammability: 1	Instability: 0

Important! The information presented herein, while not guaranteed, was prepared by competent technical personnel and is true to the best of our knowledge. NO WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SUITABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling or storage. Other factors may involve other or additional safety or performance considerations. While our technical personnel can respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State or local laws.

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

35 Neoga Street • Depew, New York 14043, USA • Phone 716-685-2121 • Fax 716-685-3236 • info@dynapurge.com • www.dynapurge.com

Dyna-Purge® is a registered trademark of Shuman Plastics, Inc.