

Safety Data Sheet

Dynatex® 49431 Super Glue

Section 1. Identification

Product Identifier Synonyms Manufacturer Stock Numbers	Dynatex® 49431 Super G 49431CL09 49431CL09	lue	
Recommended use Uses advised against	Refer to Technical Informa Refer to Technical Informa		
Manufacturer Contact Address	Dynatex a division of Sou 350 Ring Road Elizabethtown, KY, 42701 USA	dal Accumetric	
	Phone (270) 769-3385	Emergency Phone (800) 424-9300	Fax (270) 769-6418

Section 2. Hazards Identification

Classification

EYE DAMAGE/IRRITATION - Category 2A FLAMMABLE LIQUIDS - Category 4 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3 Warning

CHEMTREC

Signal Word Pictogram



Hazard Statements	Causes serious eye irritation Causes skin irritation Combustible liquid May cause respiratory irritation.
Precautionary Statements	
Response	Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Read label before use. Take off contaminated clothing and wash it before reuse.
Prevention	Avoid breathing dust/fume/gas/mist/ vapors/spray. Keep away from heat. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Wear eye protection/face protection. Wear protective gloves. Wear protective gloves/eye protection/face protection
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national /international regulations.
Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified	
Additional Information	None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
7085-85-0	Ethyl-2-Cyanoacrylate	50% - 100%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eye Contact

Flush with warm water. If eyelids are bonded closed, release eyelashes with warm water by covering the eye with a wet pad. Do not force eye open. See supplemental section for emergency action.

Skin Contact	Soak in warm water. Do not pull skin apart. See supplemental section for emergency action.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
Ingestion	Ingestion is unlikely. See supplemental section for emergency action.
First Aid Supplement	Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds to human tissue and skin in seconds. Experience has shown that accidents due to Cyanoacrylates are best handles by passive, non-surgical first aid. Treatment of specific types of accidents are suggested as follows:
Skin Contact	Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Dried adhesive does not present a health hazard even when bonded to the skin. Avoid contact with clothes, fabrics, rags, or tissue. Contact with these materials may cause polymerization. The polymerization of large amounts of adhesive will generate heat causing smoke, skin burns, and strong, irritating vapors. Wear rubber or polyethylene gloves and an apron when handling large amounts of adhesive.
Skin Adhesion	First immerse the bonded surfaces in warm, soapy water. Peel off or roll the surfaces open with the end of a blunt edge, such as a spatula or a spoon handle, then remove adhesive with soap and water. Do not try to pull the surfaces apart with a direct opposing action.
Eyelid adhesion	In the event that eyelids are stuck together or bonded to the eyeball, wash throughly with warm water and apply a gauze patch. The eye will open without further action, typically in one to two days. There will be no residual damage. Do not try to pull the surfaces apart with a direct opposing action.
Adhesive in eye	Adhesive introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, usually several hours. This will cause periods of weeping until clearance is achieved. It is important to understand that disassociation will normally occur within a matter of hours, even with gross contamination.
Mouth	If lips are accidentally stuck together apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action. It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in one to two days.
Burns	Cyanoacrylate gives off heat on solidification. In rare cases, large drops will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as described above.
Surgery	It should never be necessary to use such drastic action to separate accidentally bonded skin.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Carbon Dioxide, Dry Chemical, Foam Use water fog to cool material in vicinity of fire.
Unsuitable Extinguishing Media	None known
Unusual Fire or Explosion Hazards	None known
Special Fire Fighting Procedures	Wear self- contained breathing apparatus.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release Observe all personal protection equipment recommendations. Do not use cloths for clean up. Flood spilled material with water to polymerize. Cured material can be scrapped up and disposed of as nonhazardous waste. Make sure spill area is well ventilated.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable.

Section 7. Handling and Storage

Storage	Store away from heat and direct sunlight to maximize shelf life. Store inside in a dry location. Keep container tightly closed.
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapor or mist. Avoid contact with paper goods or fabric. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Ethyl-2-Cyanoacrylate	0.2 ppm	None	N/A
Personal Protective Equipment	Goggles, Gloves			
Eye Protection	Safety goggles or glasses with side shields are recommended.			
Skin Protection	Polyethylene or non-reactive gloves. Do not use cotton, PVC or wool.			
Ventilation	Local exhaust ventilation is recommended to maintain vapor level below TLV.			
Respiratory Protection	Not applicable with good local there is a potential to exceed a		SH approved resp	irator if

Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Clear
Odor	Characteristic
Odor Threshold	Not
	determined
Solubility	Not miscible
Partition coefficient Water/n-octanol	Not
	determined
VOC%	< 20 g/L
	(estimated)

Viscosity	Not
	determined
Specific Gravity	1.05
Density lbs/Gal	8.762
Pounds per Cubic Foot	N/A
Flash Point	87C 189F
FP Method	N/A
Ph	Not
	determined
Melting Point	Undetermined
Boiling Point	>150C 302F
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not
	determined
Flammability	Not applicable
Decomposition Temperature	Not
	determined
Auto-ignition Temperature	Product is not
	selfigniting
Vapor Pressure	0.3 hPa @
	20C
Vapor Density	Not
	determined

Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Materials to Avoid / Incompatibility	Polymerized by contact with water, alcohols, amines, and alkalis.
Chemical stability	Stable under recommended storage conditions.
Hazardous Polymerization	Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

Section 11. Toxicological Information

Special Hazard Information No known applicable information. on Components Component Toxicology No known applicable information. Information

Section 12. Ecological Information

Fate and Effects in Waste Complete information is not yet available.

Water Treatment PlantsEnvironmental EffectsComplete information is not yet available.Environmental Fate and
DistributionComplete information is not yet available.

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number	1993
UN Proper Shipping Name	Combustible Liquid, NOS
DOT Classification	N/A
Packing Group	III
Other Shipping Information	Marine pollutant: No
	Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
	DOTQuantity limitations
	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L

Section 15. Regulatory Information

California Proposition 65	Chemicals known to cause cancer: None of the ingredients is listed.	
	Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.	
	Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed.	
	Chemicals known to cause developmental toxicity: None of the ingredients is listed.	
TSCA (Toxic Substances Control Act)	All ingredients are listed.	
SARA Title III	Section 355 (extremely hazardous substances): 79-11-8 chloroacetic acid 123-31-9 1,4-dihydroxybenzene	

	Section 313 (Specific toxic chemical listings): 79-11-8 chloroacetic acid 123-31-9 1,4-dihydroxybenzene
Carcinogenic Categories	EPA (Environmental Protection Agency) 109-63-7 diethyl etherboron trifluoride I (oral)
	TLV (Threshold Limit Value established by ACGIH) 79-11-8 chloroacetic acid A4 123-31-9 1,4-dihydroxybenzene A3
	NIOSH-Ca (National Institute for Occupational Safety and Health)

Section 16. Other Information

Revision Date

12/21/2015

None of the ingredients is listed.

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.